Safety Data Sheet BELTRACO COLOR BONDER





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name:

BELTRACO COLOR BONDER (1 L)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixtures/Substance for the industrial and/or professional finishing for leather and shoes.

Uses advised against:

Stick to the recommended use.

1.3. Details of the supplier of the safety data sheet

Supplier:

Beltraco Benelux B.V.

Biestkampweg 21, 5249 JV Rosmalen, Nederland

Tel.: +31 (0)73 645 03 43 E-Mail: info@beltraco.nl www.beltraco.nl

1.3. Antigifcentrum

Dutch National Poison Information Center (UMC Utrecht)

Intended only to inform professional responders of acute poisonings

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Warning, Eye Irrit. 2, Causes serious eve irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P264 Wash hands thoroughly after handling.

P280 Wear eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards: No other hazards.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not available

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number		Classification
25% - 30%	2-(2-butoxyethoxy)ethanol	Index number: CAS: EC: REACH No.:	603-096-00-8 112-34-5 203-961-6 01-2119475104-44	① 3.3/2 Eye Irrit. 2 H319
25% - 30%	(2-methoxymethylethoxy)propanol	CAS: EC: REACH No.:	34590-94-8 252-104-2 01-2119450011-60	substance with a Community workplace exposure limit
5% - 7%	2-butoxyethanol	Index number: CAS: EC: REACH No.:	603-014-00-0 111-76-2 203-905-0 01-2119475108-36	① 3.3/2 Eye Irrit. 2 H319 ② 3.2/2 Skin Irrit. 2 H315 ② 3.1/4/Oral Acute Tox. 4 H302
1% - 3%	docusate sodium	CAS: EC: REACH No.:	577-11-7 209-406-4 01-2119491296-29	3.1/4/Inhal Acute Tox. 4 H332 3.2/2 Skin Irrit. 2 H315 3.3/1 Eye Dam. 1 H318

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

For the most important symptoms and effects, caused by exposure, see the label (section 2) and/or section 11.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2, foam, dry extinguishers, nebulised water.

Extinguishing media which must not be used for safety reasons:

Do not use jets of water as it can cause the spread of fire.

Water can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion.

Do not inhale combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

EQUIPMENT

Fire fighting clothing i. e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure air breathing apparatus (BN EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: inert absorbing material.

6.3. Methods and material for containment and cleaning up

Stop the leak or spill if this is not a risk. Use inert absorbent material to surround the contaminated area.

Collect the product wearing, if necessary, appropriate protective equipment for a possible recovering or for disposal.

Dispose in line with current laws and norms. Do not pour into drains.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working. Do not smoke.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place at a temperture between +5/40°C.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

EU - LTE(8h): 67.5 mg/m3, 10 ppm - STE: 101.2 mg/m3, 15 ppm - Notes: (for references see bibliography)

ACGIH - LTE(8h): 10 ppm - Notes: (IFV) - Hematologic, liver and kidney eff

(2-methoxymethylethoxy)propanol - CAS: 34590-94-8

EU - LTE(8h): 308 mg/m3, 50 ppm - Notes: (for references see bibliography)

ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: Skin - Eye and URT irr, CNS impair

2-butoxyethanol - CAS: 111-76-2

EU - LTE(8h): 98 mg/m3, 20 ppm - STE: 246 mg/m3, 50 ppm - Notes: (for references see bibliography)

ACGIH - LTE(8h): 20 ppm - Notes: A3, BEI - Eye and URT irr

DNEL Exposure Limit Values

Not available

PNEC Exposure Limit Values

Not available

8.2. Exposure controls

As the adoption of adequate preventive measures must always take priority over personal protective equipment, make sure that:

- in case of inhalation exposure limit values, the workplace is well ventilated through an effective local aspiration system or other technical equipment, in order to maintain airborne levels below the exposure limits values
- if inhalation exposure limit values are not applicable, a good general ventilation is generally sufficient for most operations
- an emergency shower with face and eye wash station is available
- personal protective equipment is CE marked, in compliance with applicable standards

Individual protection measures

Use in well-ventilated areas. Do not breathe vapours. Do not get in eyes and on skin. Adopt a correct personal hygiene. Do not consume or store food in the work areas.

Wash hands before smoking or eating.

Eve protection:

Use eye protecting goggles suitable to chemical risks.

Protection for skin:

Use clothing that provides comprehensive protection to the skin.

Protection for hands:

Protect hands with gloves suitable for protection against chemical agents (see standard EN 374).

In case of short-term exposure (splash protection):

Nitrile, neoprene or butyl rubber gloves

Breakthrough time: 30 min Minimum thickness: 0.4 mm In case of long-term exposure: Butyl rubber, Viton or nitrile gloves Breakthrough time: 480 min Minimum thickness: 0.7 mm

The information provided here is indicative. The following parameters should be considered when choosing work glove material: degradation, failure time and permeability.

In case of chemical mixtures, the work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and frequency of use.

Respiratory protection:

In case of inadequate ventilation, prolonged exposure or mists/vapours/aerosol exposure (eg. spray application) use a respiratory protective equipment (eg. full face mask according to the DIN EN 136 standard with A Filter for organic gases and vapours according to DIN EN 141).

Thermal Hazards:

None

Environmental exposure controls:

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be

checked to ensure compliance with environmental standards.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	fluid		
	colourless	UNI EN ISO 15528:2003 (3.11+6.7)/UNI EN ISO 1513:1996	
Odour:	charatteristic		
Odour threshold:	Not available		
pH:	7.5 ± 1 (1:10)	UNI EN 1245:2011	
Melting point / freezing point:	<0 °C	Expert judgement	
Initial boiling point and boiling range:	>100 °C	Expert judgement	
Flash point:	>65 °C	Expert judgement	
Evaporation rate:	Not available	- (R)	
Solid/gas flammability:	Not Relevant*	- 0	
Upper/lower flammability or explosive limits:	Not available		
Vapour pressure:	Not available		
Vapour density:	Not available		
Relative density:	1.00 ± 0.05 g/cm3	UNI EN ISO 2811-1	
Solubility in water:	miscible	(1:10) water	
Solubility in oil:	miscible in glycolethers	Expert judgement	
Partition coefficient (n-octanol/water):	Not available		
Auto-ignition temperature:	Not available		
Decomposition temperature:	Not Relevant*		
Viscosity:	Not available		
Explosive properties:	Not Relevant*		
Oxidizing properties:	Not Relevant*		

^{*}Data not applicable or not relevant due to the nature of the product and / or on account of its chemical composition.

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	Not available		
Fat Solubility:	Not available		
Conductivity:	Not available		
Substance Groups relevant properties	Not available		

^{*}Data not applicable or not relevant due to the nature of the product and / or on account of its chemical composition.

VOC total content: 54-56%

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None in particular in the normal conditions of use.

10.4. Conditions to avoid

The product is stable under normal storage/use conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

May produce toxic and noxious fumes in case of fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

In the absence of experimental data for the product itself, health hazards are evalueted according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

Serious eye damage/irritation

Stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Further information

Inhalation: may cause drowsiness and headaches.

Test data: Not available

Toxicological information of the main substances found in the mixture:

2-(2-butoxyethoxy)ethanol - CAS: 112-34-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

2-butoxyethanol - CAS: 111-76-2

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rat = 2270 mg/kg Test: LD50 - Route: Skin - Species: Rabbit = 470 mg/kg Test: LD50 - Route: Oral - Species: Rat = 2270 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 2.21 mg/l - Duration: 4h

docusate sodium - CAS: 577-11-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 200 mg/kg

Further information No one in particular.

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

12.1. Toxicity

Adopt sound working practices, so that the product is not released into the environment.

Not available

12.2. Persistence and degradability

Not available

12.3. Bioaccumulative potential

Not available

12.4. Mobility in soil

Not available

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

This material is NOT RESTRICTED for transportation (ADR/RID, IMDG, IATA, ICAO).

14.2. UN proper shipping name

Not available

14.3. Transport hazard class(es)

Not available

14.4. Packing group

Not available

14.5. Environmental hazards

Not available

14.6. Special precautions for user

Not available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 55

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

Not available

15.2. Chemical safety assessment

No

SECTION 16: Other information

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection SECTION 9: Physical and chemical properties

SECTION 11: Toxicological information SECTION 13: Disposal considerations **SECTION 14: Transport information** SECTION 15: Regulatory information

ADR: European Agreement concerning the International Carriage of Dangerous

Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNFI: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association"

(IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

Regulation Concerning the International Transport of Dangerous Goods by Rail. RID:

STE: Short-term exposure. Short Term Exposure limit. STEL: STOT: Specific Target Organ Toxicity. TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH

Standard).

WGK: German Water Hazard Class.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances (1983)

I.N.R.S. - Fiche Toxicologique

ECHA database on registered substances (http://apps.echa.europa.eu/registered/registered-sub.aspx)

ECHA Classification and Labelling Inventory (http://echa.europa.eu/clp/c I inventory en.asp)

GESTIS hazardous substances database of German Berufsgenossenschaften

(http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Stoffdatenbank/index-2.jsp)

Classification according to Regulation (EC) Nr. 1272/2008

Classification procedure

Eye Irrit. - H319

Calculation method

Text of phrases referred to under heading 3:

H319 Causes serious eye irritation.


H315 Causes skin irritation.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H318 Causes serious eye damage.



Further information

This product must be kept, handled and used in accordance with health and safety regulations, sound industrial practice and conforming to the laws in force.

The information given is based on our present knowledge, at the time of sending the data sheet and only serves for describing the product for security reasons, without guaranteeing specific properties.

Due to the various uses of our product and for factors not dependent on us, no responsibility is accepted for the use of this information.

Please keep your records up to date and make this sheet available to all relevant personnel. This safety sheet cancels and substitutes any other previous issue.

