

**Safety Data Sheet**  
**BELTRACO LEATHER DEGREASER SPRAY 200 ML - 400 ML**



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification:

Trade name:

BELTRACO LEATHER DEGREASER (SPRAY 400 ML)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Mixtures for the industrial and/or professional care and maintenance of leather items.

Uses advised against:

Stick to the recommended use.

1.3. Details of the supplier of the safety data sheet

Supplier:

Beltraco Benelux B.V.

Biestkampweg 21, 5249 JV Rosmalen, Nederland

Tel.: +31 (0)73 645 03 43

E-Mail: info@beltraco.nl

www.beltraco.nl

1.4. Antigifcentrum

Dutch National Poison Information Center (UMC Utrecht)

Intended only to inform professional responders of acute poisonings

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

-  Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.
-  Warning, Skin Irrit. 2, Causes skin irritation.
-  Warning, STOT SE 3, May cause drowsiness or dizziness.
-  Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

P391 Collect spillage.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Special Provisions:

None

Contains

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not available

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification (The higher extreme values, if indicated, are to be considered excluded):

Qty	Name	Ident. Number	Classification
40% - 50%	Hydrocarbons, C6, isoalkanes, <5% n-hexane	CAS: 64742-49-0 EC: 931-254-9 REACH No.: 01-2119475103-34	 2.6/2 Flam. Liq. 2 H225  3.10/1 Asp. Tox. 1 H304  3.2/2 Skin Irrit. 2 H315  3.8/3 STOT SE 3 H336  4.1/C2 Aquatic Chronic 2 H411
25% - 30%	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280
15% - 20%	butane	Index number: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	 2.2/1 Flam. Gas 1 H220  2.5 Press. Gas H280
5% - 7%	ethyl acetate	Index number: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH No.: 01-2119475103-46	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066

For the full text of the hazard statements (H) see section16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

In case of respiratory problems, medical care is needed.

#### 4.2. Most important symptoms and effects, both acute and delayed

For the most important symptoms and effects, caused by exposure, see the label (section 2) and/or section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Treat symptomatically.

---

## SECTION 5: Firefighting measures

---

### 5.1. Extinguishing media

Suitable extinguishing media:

CO<sub>2</sub>, foam, dry extinguishers, nebulised water.

Extinguishing media which must not be used for safety reasons:

Do not use jets of water as it can cause the spread of fire.

Water can be used to cool containers exposed to flames to prevent explosions.

### 5.2. Special hazards arising from the substance or mixture

IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion.

Do not inhale combustion gases.

Burning produces heavy smoke.

### 5.3. Advice for firefighters

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

EQUIPMENT

Fire fighting clothing i. e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure air breathing apparatus (BN EN 137).

---

## SECTION 6: Accidental release measures

---

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

Remove persons to safety.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: inert absorbing material.

### 6.3. Methods and material for containment and cleaning up

Stop the leak or spill if this is not a risk. Use inert absorbent material to surround the contaminated area.  
Provide adequate room ventilation, where the spill has occurred.

### 6.4. Reference to other sections

See also section 8 and 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not eat or drink while working. Do not smoke.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Avoid contemporary handling of any incompatible materials (see section 10).

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Wash hands thoroughly after shift.

See also section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place at a temperature between +5/40°C.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular. See also section 10.

Instructions as regards storage premises:

Cool and adequately ventilated.

### 7.3. Specific end use(s)

None in particular, except those listed in paragraph 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Source: GESTIS International Limit Values Database

propane - CAS: 74-98-6

ACGIH - Notes: (D, EX) - Asphyxia

VLE short - 1000 ppm

butane - CAS: 106-97-8

ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

ethyl acetate - CAS: 141-78-6

ACGIH - TWA(8h): 400 ppm - Notes: URT and eye irr

TLV-ACGIH - TWA: 1441 mg/m<sup>3</sup>, 400 ppm

EU - TWA(8h): 734 mg/m<sup>3</sup>, 200 ppm - STEL: 1468 mg/m<sup>3</sup>, 400 ppm

Deutschaland (AGS) - TWA: 1500 mg/m<sup>3</sup>, 400 ppm - STEL(): 3000 mg/m<sup>3</sup>, 500 ppm

Deutschaland (DFG) - TWA: 750 mg/m<sup>3</sup>, 200 ppm - STEL(): 1500 mg/m<sup>3</sup>, 400 ppm

España - TWA: 1460 mg/m<sup>3</sup>, 400 ppm

France - TWA: 1400 mg/m<sup>3</sup>, 400 ppm

Österreich - TWA: 1050 mg/m<sup>3</sup>, 300 ppm - STEL: 2100 mg/m<sup>3</sup>, 600 ppm - Notes: TWA = MAK Langzeitwert

STEL = Kurzzeitwert

Polska - TWA: 200 ppm - STEL: 600 ppm

România - TWA: 400 mg/m<sup>3</sup>, 111 ppm - STEL(): 500 mg/m<sup>3</sup>, 139 ppm

Sverige - TWA: 500 mg/m<sup>3</sup>, 150 ppm - STEL(): 1100 mg/m<sup>3</sup>, 300 ppm

United Kingdom - TWA: 730 mg/m<sup>3</sup>, 200 ppm - STEL: 1460 mg/m<sup>3</sup>, 400 ppm  
 People's Republic of China - TWA: 200 mg/m<sup>3</sup> - STEL(): 300 mg/m<sup>3</sup>

Legal base:

TLV-ACGIH: ACGIH 2014 and updates

UE European Union: Directive 2000/39/CE\*\*

Deutschland (AGS): Technische Regeln für Gefahrstoffe, Arbeitsplatzgrenzwerte, TRGS 900\*\*

Deutschland (DFG): MAK-und BAT-Werte-Liste 2012\*\*

España: INSHT Limites de exposición profesional para agentes químicos en España 2015\*\*

France: Valeurs limites d'exposition professionnelle aux agents chimiques en france. ED 984. INRS (2006)\*\*

Italia: Decreto Ministeriale 26/02/2004\*\*

Nederland: Nationale wettelijke publieke grenswaarden\*\*

Österreich: Grenzwerteverordnung 2003 - GVK 2003\*\*

România: HOTARÂRE Nr. 1218 din 6 septembrie 2006 and Complement from 2012 at [www.mmuncii.ro](http://www.mmuncii.ro)\*\*

Sverige: Occupational Exposure Limit Values, Statute Book of the Swedish Work Environment Authority, AFS 2011:18, English Translation\*\*

United Kingdom: EH40/2005 Workplace exposure limits\*\*

\*\*and updates

DNEL Exposure Limit Values

ethyl acetate - CAS: 141-78-6

Worker Industry: 1468 mg/m - Consumer: 734 mg/m - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 1468 mg/m - Consumer: 734 mg/m - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 63 mg/kg - Consumer: 37 mg/m - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 734 mg/m - Consumer: 367 mg/m - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 734 mg/m - Consumer: 367 mg/m - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 4.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

ethyl acetate - CAS: 141-78-6

Target: Fresh Water - Value: 0.24 mg/l

Target: Marine water - Value: 0.024 mg/l

Target: Freshwater sediments - Value: 1.15 mg/kg

Target: Marine water sediments - Value: 0.115 mg/kg

Target: Soil (agricultural) - Value: 0.148 mg/kg

Target: Microorganisms in sewage treatments - Value: 650 mg/l

Target: Food chain - Value: 0.2 g/kg - Type of hazard: Secondary poisoning

## 8.2. Exposure controls

As the adoption of adequate preventive measures must always take priority over personal protective equipment, make sure that:

- in case of inhalation exposure limit values, the workplace is well ventilated through an effective local aspiration system or other technical equipment, in order to maintain airborne levels below the exposure limits values
- if inhalation exposure limit values are not applicable, a good general ventilation is generally sufficient for most operations
- an emergency shower with face and eye wash station is available
- personal protective equipment is CE marked, in compliance with applicable standards

Individual protection measures

Use in well-ventilated areas. Do not breathe vapours. Do not get in eyes and on skin.

Adopt a correct personal hygiene. Do not consume or store food in the work areas.

Wash hands before smoking or eating.

Eye protection:

Use eye protecting goggles suitable to chemical risks.

Protection for skin:

Use clothing that provides comprehensive protection to the skin.

Protection for hands:

Protect hands with gloves suitable for protection against chemical agents (see standard EN 374).

In case of short-term exposure (splash protection):

Nitrile, neoprene or butyl rubber gloves

Breakthrough time: 30 min

Minimum thickness: 0.4 mm

In case of long-term exposure:

Butyl rubber, Viton or nitrile gloves

Breakthrough time: 480 min

Minimum thickness: 0.7 mm

The information provided here is indicative. The following parameters should be considered when choosing work glove material: degradation, failure time and permeability.

In case of chemical mixtures, the work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and frequency of use.

Respiratory protection:

In case of inadequate ventilation, prolonged exposure or mists/vapours/aerosol exposure (eg. spray application) use a respiratory protective equipment (eg. full face mask according to the DIN EN 136 standard with A Filter for organic gases and vapours according to DIN EN 141).

Thermal Hazards:

None

Environmental exposure controls:

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	aerosol, colourless	UNI EN ISO 15528:2003 (3.11+6.7)/UNI EN ISO 1513:1996	--
Odour:	of solvent	--	--
Odour threshold:	Not available	--	--
pH:	Not Relevant*	--	--
Melting point / freezing point:	<0 °C	Expert judgement	--
Initial boiling point and boiling range:	<35 °C	Expert judgement	--
Flash point:	Not available	--	--
Evaporation rate:	Not available	--	--
Solid/gas flammability:	Not Relevant*	--	--
Upper/lower flammability or explosive limits:	Not available	--	--
Vapour pressure:	Not available	--	--
Vapour density:	Not available	--	--
Relative density:	0.65 +/- 0.05 g/cm <sup>3</sup>	UNI EN ISO 2811-1	--
Solubility in water:	not miscible	--	--

Solubility in oil:	miscible in organic solvents	--	--
Partition coefficient (n-octanol/water):	Not available	--	--
Auto-ignition temperature:	Not available	--	--
Decomposition temperature:	Not available	--	--
Viscosity:	Not available	--	--
Explosive properties:	Not Relevant*	--	--
Oxidizing properties:	Not Relevant*	--	--

\*Data not applicable or not relevant due to the nature of the product and / or on account of its chemical composition.

#### 9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	Not available	--	--
Fat Solubility:	Not available	--	--
Conductivity:	Not available	--	--
Substance Groups relevant properties	Not available	--	--

\*Data not applicable or not relevant due to the nature of the product and / or on account of its chemical composition.

VOC total content: 92-94%

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None in particular in the normal conditions of use.

### 10.4. Conditions to avoid

The product is stable under normal storage/use conditions.

Do not expose at temperatures over 50° C: the elevated vapour pressure may cause the explosion of the packaging due to the temperature rise.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

May produce toxic and noxious fumes in case of fire.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

#### Skin corrosion/irritation

Contact with skin may cause: irritation, erythema, edema, dryness and chapped skin.

Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

#### STOT-single exposure

This product contains highly volatile substances, which may cause serious depression of the central nervous system (CNS) and have negative effects, such as drowsiness, dizziness, slow reflexes, narcosis.

Further information

No one in particular.

Toxicological information of the product:

- a) acute toxicity  
Not classified  
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation  
The product is classified: Skin Irrit. 2 H315
- c) serious eye damage/irritation  
Not classified  
Based on available data, the classification criteria are not met
- d) respiratory or skin sensitisation  
Not classified  
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity  
Not classified  
Based on available data, the classification criteria are not met
- f) carcinogenicity  
Not classified  
Based on available data, the classification criteria are not met
- g) reproductive toxicity  
Not classified  
Based on available data, the classification criteria are not met
- h) STOT-single exposure  
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure  
Not classified  
Based on available data, the classification criteria are not met
- j) aspiration hazard  
Not classified  
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

ethyl acetate - CAS: 141-78-6

- a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 5620 mg/kg  
Test: LC50 - Route: Inhalation - Species: Rabbit = 1600 mg/kg

Further information

Hydrocarbons, C6, isoalkanes, <5% n-hexane: benzene content is <0.01% w/w.

---

## SECTION 12: Ecological information

---

### 12.1. Toxicity

Adopt sound working practices, so that the product is not released into the environment.

The product is classified: Aquatic Chronic 2 - H411

### 12.2. Persistence and degradability

None

Not available

### 12.3. Bioaccumulative potential

Not available

### 12.4. Mobility in soil

Not available

- 12.5. Results of PBT and vPvB assessment  
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects  
None

---

### SECTION 13: Disposal considerations

---

- 13.1. Waste treatment methods  
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

### SECTION 14: Transport information

---

- 14.1. UN number  
ADR/RID UN number: 1950  
IMDG-Un number: 1950  
IATA-Un number: 1950
- 14.2. UN proper shipping name  
ADR/RID-Technical name: AEROSOLS, FLAMMABLE - FREE - CAP. 3.4  
IATA-Technical name: AEROSOLS, FLAMMABLE - FREE LQ2 - CAP. 3.4  
IMDG-Technical name: AEROSOLS, FLAMMABLE - FREE LQ2 - CAP. 3.4
- 14.3. Transport hazard class(es)  
ADR-Class: 2  
ADR-Label: 2.1  
Rail (RID): 2  
Air (ICAO/IATA): 2.1  
IATA-Label: 2.1  
IMDG-Class: 2.1  
IMDG-Label: 2.1
- 14.4. Packing group  
ADR/RID-Packing Group: --  
IATA-Packing group: --  
IMDG-Packing group: --
- 14.5. Environmental hazards
- 14.6. Special precautions for user  
ADR/RID-Tunnel Restriction Code: (D)  
IMDG-Technical name: AEROSOLS, FLAMMABLE - FREE LQ2 - CAP. 3.4  
IMDG-EMS: F-D,S-U  
Segregation Group: None .
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
No

---

### SECTION 15: Regulatory information

---

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)  
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
 Regulation (EU) n. 2016/918 (ATP 8 CLP)  
 Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
 Regulation (EU) n. 2017/776 (ATP 10 CLP))  
 Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P3a, E2

## 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Based on information we have, a Chemical Safety Assessment, if expected, has been carried out for the substances in the mixture by the manufacturer or the importer.

## SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2

Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking  
SECTION 3: Composition/information on ingredients  
SECTION 8: Exposure controls/personal protection  
SECTION 9: Physical and chemical properties  
SECTION 11: Toxicological information  
SECTION 12: Ecological information  
SECTION 15: Regulatory information  
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Aerosols 1, H222+H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
STOT SE 3, H336	Calculation method
Aquatic Chronic 2, H411	Calculation method

This document was prepared by a competent person who has received appropriate training.

#### Further information

The information is considered correct, but it is not exhaustive and it shall be used only as a guide which is based on the current knowledge of the substance or mixture and it is applicable to the safety precautions appropriate for the product.

The information given is based on our present knowledge, at the time of sending the data sheet and only serves for describing the product for security reasons, without guaranteeing specific properties.

Due to the various uses of our product and for factors not dependent on us, no responsibility is accepted for the use of this information.

Please keep your records up to date and make this sheet available to all relevant personnel. This safety sheet cancels and substitutes any other previous issue.

#### Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances (1983)

I.N.R.S. - Fiche Toxicologique

ECHA database on registered substances (<http://apps.echa.europa.eu/registered/registered-sub.aspx>)


ECHA Classification and Labelling Inventory ([http://echa.europa.eu/clp/c\\_l\\_inventory\\_en.asp](http://echa.europa.eu/clp/c_l_inventory_en.asp))

GESTIS hazardous substances database of German Berufsgenossenschaften

(<http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Stoffdatenbank/index-2.jsp>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ATE: Acute Toxicity Estimate  
ATEmix: Acute toxicity Estimate (Mixtures)

CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.



beltraco